



We develop, test and optimize for the well-ness of your horses.

Wellness for your horse is not only our slogan, it's the focus of our work. Wellness involves much more than just comfort and wellbeing. It is about environmental protection, sustainability, the avoidance of pollutants (PAHs) as well as economic efficiency in the stables.

Rubber is what makes us special.

1. Environmentally friendly

Special recycling process preserves valuable resources.

The rubber base material in the tyre contains a lot of valuable rubber, making it an ideal raw material for products in horse husbandry, where high resilience and a long service life are a prerequisite. In addition, resources are preserved: unlike with typical mats made of new rubber, with BELMONDO® mats no rainforest has to make way for further rubber plantations.

Food-grade vegetable oils as plasticizers.

The term "plasticizer" has negative connotations because inferior mineral oils usually contain unnecessarily high amounts of PAHs that are harmful to the environment and health. Safety for the environment and health is important to us: instead of traditional plasticizers, we use only vegetable oils – naturally from European cultivation.

2. Economical

Less bedding and less work: an investment in rubber flooring quickly pays for itself.

Our rubber mats provide the necessary softness and heat insulation, the bedding only has to bind any liquid that is produced. This system with a soft rubber mat and reduced amount of bedding saves a lot of work when mucking out. Also positive: less dust and less manure result in a healthier stable environment!

3. Comfortable

BELMONDO® rubber flooring creates more safety and comfort for your horse throughout the stable.

Our rubber mats have been specially developed for horses and are therefore perfectly adapted to the specific areas of application.

This means for you:

- more horse comfort and less effort in the loosebox
- more comfort and less noise in the stable walkway
- more safety for key areas (such as washdowns and service area)
- robust, durable and easy-care flooring for daily use
- quick and easy installation thanks to the puzzle principle

4. Excellent

In addition to constant monitoring in our in-house laboratory, we also have our products tested externally for independent confirmation.

Our products have passed the PAH test of the DLG with flying colours.



Important product properties such as slip resistance or acid resistance are externally certified by the DLG.



Many of our products have been licensed by the specialist department for animal-friendly husbandry and animal protection.



We are certified according to the globally valid quality and energy standards ISO 9001 and ISO 50001.





BELMONDO® puzzle on 4 sides

loosebox and bedded area





BELMONDO® Basic

BELMONDO® Classic

BELMONDO® Trend






Basic loosebox comfort

Tried and tested highly robust

reinforced surface















 (\mathbf{i})

BELMONDO°

Motion / Horsewalker

If you have any questions regarding the electric

conductivity, we are happy

to be at your disposal.

Trafficability

BELMONDO® mats (except Kingsize Duo, Walkway, Kingsize) are basically suitable for vehicle traffic. Please comply with our guidelines for trafficability!

All products are suitable for every type of shoe.

Please take notice of the corresponding specifications and installation instructions with useful advice and tips. You will obtain these at your local BELMONDO® dealer or at www.kraiburg-belmondo.com.



Thickness 18 mm

Dimension 1 x 1 m

norseshoe



Lower side:



Surface: horseshoe profile with



Thickness 18 mm

Dimension 1 x 1 m

Lower side:



Surface: horseshoe profile with



Lower side: air cushions with rubber

Thickness 28 mm **Dimension** 1 x 1 m

stable walkway













when wet









Thickness 12 mm

Dimension 1 x 1 m



Thickness 16 mm **Dimension** 1 x 1 m

Surface:

mosaic design

stable paddock / walkways / washdown



BELMONDO® Paddock



The all-rounder also for outdoors

UV- and weatherresistant





Surface: rhombic profile (36) with top coat



Lower side: studs (5 mm)

Thickness 24 mm **Dimension** 1 x 1 m Accessories

BELMONDO® Drain gutter/Gully





For BELMONDO® Walkpro, Paddock

Dimension:

Drain gutter 16.7 x 100 cm

Gully 40 x 40 cm

VITA Top



Optical border towards the wall

Dimension:

Height 5 cm

Width x length 5.5 x 200 cm

BELMONDO® tailor-made

BELMONDO® jointless

BELMONDO® special applications

horse walker




BELMONDO® Motion



Basic comfort in the horse walker

BELMONDO® Horsewalker



The Classic – with reinforced surface

also for intensively used horse walkers





Surface:

rhombic profile

Lower side:

multisquare

profile (3 mm)

50) with top coat





Thickness 21 mm **Dimension** individually tailor-made

Thickness 21 mm Dimension individually tailor-made





BELMONDO® Kingsize Cover



Large-area flooring for the loosebox

heat insulating and improved grip







Thickness 15 mm Dimension 262/348/440/525 x 250 - 600 cm

in 10-cm increments



Extra soft


stable)

FOKUS TEST

especially for bedded

areas (e.g. in the open

Surface and lower side: pebbled profile



bedded areas

BELMONDO®

Kingsize Duo

Thickness ca. 4 cm Dimension of the complete system: infinitely expandable

(from 525 x 600 cm: joint


covering with maxiPROFIL)

Thickness ca. 6.5 cm Dimension of the complete system: max. 525 x 600 cm

aneasthesia / recovery pen



BELMONDO[®] Kingsize



Especially for animal clinics

with three functional layers for added softness

Surface and

pebbled profile

lower side:





soil

natural

sloping walkways / ramps



BELMONDO® **BELMONDO®** Flix



"Shock absorber" on the wall

protects your horse's legs and the loosebox walls


wall



Stabiliz es natural soil

especially for areas that tend to get muddy





More safety - uphill and downhill

practically tested on slopes of up to 15 %



Rodeo



Surface: wooden planks



Thickness 12 mm

Dimension

130 x 350 cm



Surface:



Lower side:



rib profile with top coat



Lower side:

Thickness 24 mm

Dimension 110 x 175 cm

Hole size Ø ca. 30 mm Thickness 24 mm

Dimension 65/130 x 200 cm





BELMONDO® is a trademark of



Gummiwerk KRAIBURG Elastik GmbH & Co. KG Göllstraße 8, 84529 Tittmoning Germany Tel.: +49 8683 701-303 belmondo@kraiburg-elastik.de www.kraiburg-belmondo.com 06/2022





Made in Germany

We have been developing and manufacturing rubber flooring for animal husbandry at our Tittmoning site for more than 50 years. With more than 200 employees, we are one of the leading suppliers of stable flooring. KRAIBURG BELMONDO® rubber flooring for horses is a quality product, made in Germany. As a German manufacturer, we guarantee many years of reliable use of our products and take pride in the excellent reviews from testing institutes.

Tolerances: thickness: +3/-2 mm (except for approximate figures); width + length: +/-1.5 % (DIN ISO 3302-1 tolerance class M4)

More technical details on request. The products presented here should only be used for the mentioned applications. Technical specifications are subject to alterations. All sales are subject to our General Terms and Conditions. Legal basis is the German version of the document.